

Shear Beam

SHEARBEAM

- Suitable for floor scales, vehicle-test line, hopper scales and other electronic weighing devices.
- Highly accurate and reliable.
- Stainless steel construction.
- Sealed to IP68.



Specifications:	OIML R60 C3	OIML R60 C4	OIML R60 C5	OIML R60 C6
Output sensitivity (=FS):	2,0 ± 0,04 mV/V	2,0 ± 0,04 mV/V	3,0 ± 0,08 mV/V	3,0 ± 0,08 mV/V
Maximum capacity (Emax):	0,5T, 1T, 1,5T, 2T, 2,5T, 3T, 5T, 7,5T, 10T			0,5, 1, 1,5, 2, 2,5T
Max. Number of load cell interval:	3000 nLC	4000 nLC	5000 nLC	6000 nLC
Ratio of min. LC verification interval:	1000	15000	20000	20000
Combined Error:	≤± 0.0230 %FS	≤± 0.0175 %FS	≤± 0.0140 %FS	≤± 0.0116 %FS
Minimum dead load:	0% of Emax			
Safe overload:	150% of Emax			
Ultimate overload:	300% of Emax			
Zero balance:	<± 1.0% of FS			
Excitation, recommended voltage:	5 to 12 V			
Excitation maximum:	18 V			
Input resistance:	350 ± 3.5 Ω			
Output resistance:	350 ± 3.5 Ω			
Insulation resistance:	≥ 5000 (at 50VDC) MΩ			
Compensated temp.:	-10 to 40°C			
Operating temp.:	-35 to 65°C			
Storage temp.:	-40 to 75°C			

Item No:	Capacity (T)	L x B x H (mm)	ØD (mm)	M
SHEARBEAM-xxT-z1	0,5, 1, 1,5, 2	130 x 31,3 x 31,3	13,5	M12
SHEARBEAM-xxT-z1	2,5, 5	171 x 36,8 x 36,8	20,5	M20
SHEARBEAM-xxT-z1	7,5, 10	222 x 49,5 x 49,5	26,9	M24

