

## Dynamometer

D2000A

- Under hook crane weighing. Crane and hoist calibration and proof load testing.
- Highly accurate and reliable,  $\pm 0,2\%$  FS accuracy.
- Very clear red digit LED display. Visible at long distances / in bright daylight.
- Robust high strength steel construction for use in hostile environments.
- Flexible suspension, designed to minimize torsional effects.
- Supplied with full certificate of calibration.
- Designed and manufactured in DK for high quality assurance.



### Specifications:

Capacity:	2T, 6,5T, 12,5T, 25T, 55T and 120T
Accuracy:	$\pm 0,2\%$
Safe overload:	120%
Materials:	High strength steel. Silver chrome plated surface.
IP class:	IP 64
Display:	Bright LED.
Operating time:	8-14 hours.
Operation temp.	-20°C to 40°C
Batteries:	AA 1,5V (rechargeable)
Charger:	NIMH, 4-10 cell.

Item No:	Capacity (T)	Dimensions (LxWxH)	Bolt dia. (mm)	Weight (kg.)	Increment (kg.)
D2000-ALU-2T	2	200x100x66	20,00	1,20	1
D2000A-6T	6,5	220x95x75,4	30,00	3,30	5
D2000A-12T	12,5	250x95x83	35,50	4,55	10
D2000A-25T	25	340x108x83	51,00	7,60	10
D2000A-55T	55	440x160x94,4	73,00	19,10	50
D2000A-120T	120	500x200x120,2	100,00	39,50	100

### Accessory options:

2000B-6V-RTX	Remote display, wireless
DYNALOG	PC datalog software

