

Large Display

D2, D4

vetec

- Vetec Large Display is ideal in combination with load cells.
- Provided with and without Relay Output (alarms) and special output options.
- Remote setting from ground level.
- Very easy to programme and use. No-menu programming.



| Specification | |
|-----------------|---|
| Digits | Available with 4 and 6 digits. |
| Input signals: | <ul style="list-style-type: none"> • Load cells. • 4-20mA, 0-10V, 1-5V etc. • Serial Data RS232, RS485, 422 etc. |
| Output options: | <ul style="list-style-type: none"> • 2 or 4 alarms SPST relays, 2x SPDT. • 4-20mA, 0-10V or -10 to +10 analog. • RS232, RS485, Ethernet data output. |
| IP Class: | IP65 for bottom glands, IP54 for top. |
| Materials: | Black polycarbonate. |

Examples, all with load cell input.

| Item No. | Digits | Digit Height | Viewing | Power Supply | Relay Output | Analogue Output |
|--------------------|--------|--------------|-----------|--------------|--------------|-----------------|
| D2/4-L-R-AC-3 | 4 | 57 mm | 25 Meters | 95-265 VAC | 0 | - |
| D4/4-L-R-AC-3 | 4 | 102 mm | 50 Meters | 95-265 VAC | 0 | - |
| D4/6-L-R-AC-3 | 6 | 102 mm | 50 Meters | 95-265 VAC | 0 | - |
| D4/6-L-R-48VAC-3 | 6 | 102 mm | 50 Meters | 48 VAC | 0 | - |
| D2/4-L-AL2-R-AC-3 | 4 | 57 mm | 25 Meters | 95-265 VAC | 2 | - |
| D4/4-L-AL2-R-AC-3 | 4 | 102 mm | 50 Meters | 95-265 VAC | 2 | - |
| D4/6-L-AL2-R-AC-3 | 6 | 57 mm | 25 Meters | 95-265 VAC | 2 | - |
| D4/6-L-AL2-R-48-3 | 6 | 102 mm | 50 Meters | 48 VAC | 2 | - |
| D4/4-L-ANI-AC-3 | 4 | 102 mm | 50 Meters | 95-265 VAC | 0 | 4-20Ma |
| D4/4-L-485-AC-3 | 4 | 102 mm | 50 Meters | 95-265 VAC | 0 | RS485 |
| D4/4-L-A2-RTU-AC-3 | 4 | 102 mm | 50 Meters | 95-265 VAC | 2 | MODBUS RTU |
| D4/6-L-A2-RTU-AC-3 | 6 | 102 mm | 50 Meters | 95-265 VAC | 2 | MODBUS RTU |

* Other displays can be provided to meet specific requirements and other applications.