

## Large Display

D2, D4

- Vetec Large Display is ideal in combination with load cells.
- Provided with and without Relay Output (alarms) and special output options.
- Remote setting from ground level.
- Very easy to programme and use. No-menu programming.



Specification	
Digits	Available with 4 and 6 digits.
Input signals:	<ul style="list-style-type: none"> <li>• Load cells.</li> <li>• 4-20mA, 0-10V, 1-5V etc.</li> <li>• Serial Data RS232, RS485, 422 etc.</li> </ul>
Output options:	<ul style="list-style-type: none"> <li>• 2 or 4 alarms SPST relays, 2x SPDT.</li> <li>• 4-20mA, 0-10V or -10 to +10 analog.</li> <li>• RS232, RS485, Ethernet data output.</li> </ul>
IP Class:	IP65 for bottom glands, IP54 for top.
Materials:	Black polycarbonate.

Examples, all with load cell input.

Item No.	Digits	Digit Height	Viewing	Power Supply	Relay Output	Analogue Output
D2/4-L-R-AC-3	4	57 mm	25 Meters	95-265 VAC	0	-
D4/4-L-R-AC-3	4	102 mm	50 Meters	95-265 VAC	0	-
D4/6-L-R-AC-3	6	102 mm	50 Meters	95-265 VAC	0	-
D4/6-L-R-48VAC-3	6	102 mm	50 Meters	48 VAC	0	-
D2/4-L-AL2-R-AC-3	4	57 mm	25 Meters	95-265 VAC	2	-
D4/4-L-AL2-R-AC-3	4	102 mm	50 Meters	95-265 VAC	2	-
D4/6-L-AL2-R-AC-3	6	57 mm	25 Meters	95-265 VAC	2	-
D4/6-L-AL2-R-48-3	6	102 mm	50 Meters	48 VAC	2	-
D4/4-L-ANI-AC-3	4	102 mm	50 Meters	95-265 VAC	0	4-20Ma
D4/4-L-485-AC-3	4	102 mm	50 Meters	95-265 VAC	0	RS485
D4/4-L-A2-RTU-AC-3	4	102 mm	50 Meters	95-265 VAC	2	MODBUS RTU
D4/6-L-A2-RTU-AC-3	6	102 mm	50 Meters	95-265 VAC	2	MODBUS RTU

\* Other displays can be provided to meet specific requirements and other applications.