

LOADLINK INOX

Ver. 1.0

- Highly accurate and reliable, $\pm 0,2\%$ FS accuracy.
- IP67 Classification. Ideal for wet environments.
- Robust high strength Stainless Steel construction for use in hostile environments.
- Supplied with full certificate of calibration.
- Designed and manufactured in Denmark for high quality assurance.



Specifications					
Item No.	25670301 / 25670302	25670601 / 25670602	25671201 / 25671202	25672501 / 25672502	25675501 / 25675502
Capacity	3.25T	6.5T	12.5T	25T	55T
Accuracy	$\pm 0.2\%$ FS				
Safe overload	110%				
Safe overload	3575 kg.	7150 kg.	13750 kg.	27500 kg.	60500 kg.
Breaking limit	500%				
Material	High strength Stainless Steel housing.				
IP Classification	IP67				
Output	1 mV/V or 4-20mA				
Cable	5m (4,6mm Poly Cable)				
Operating temp.	-20°C to $+50^{\circ}\text{C}$				

Item No.:	Capacity (T)	A (mm)	B (mm)	C (mm)	D (mm)	Ø (mm)	Weight (kg)
25670301 / 25670302	3.25T	230.00	93.00	170.00	33.00	20.00	2.13
25670601 / 25670602	6.5T	275.00	120.00	190.00	38.00	27.00	5.08
25671201 / 25671202	12.5T	300.00	125.00	200.00	38.00	37.00	6.99
25672501 / 25672502	25T	360.00	135.00	230.00	38.00	54.00	9.73
25675501 / 25675502	55T	460.00	175.00	280.00	50.00	74.00	22.63

