

Uni-Link with S-Cell

Ver. 1.5

- Highly accurate and reliable, $\pm 0,06\%$ FS accuracy.
- Very clear red digit LED display. Visible at long distances / in bright daylight.
- IP67 Classification. Ideal for wet environments.
- Supplied with full certificate of calibration.
- Includes a durable ABS plastic hard case.
- Designed and manufactured in Denmark for high quality assurance.
- Bluetooth allows long-range (Class 1) and short-range (Class 2) communication with Vetec App for data logging.
- Optional handheld remote display available.



Specifications			
Item No.	UNI-LINK02-1000S	UNI-LINK02-2000S	UNI-LINK02-5000S
Capacity	1000 kg.	2000 kg.	5000 kg.
Accuracy	$\pm 0.06\%$ FS		
Accuracy	± 0.6 kg.	± 2 kg.	± 3 kg.
Safe overload	150 %		
Safe overload	1500 kg.	3000 kg.	7500 kg.
Breaking limit	500%		
Resolution	0.1 kg.	1 kg.	1 kg.
Material	Steel, Stainless steel and PETG plastic		
IP Classification	IP67		
Display	Bright LED		
Digit height	14 mm		
Digit color	Red		
Operating time	16-20 hours (Operating at low temperatures will decrease the operating time)		
Operating temp.	-20°C to $+50^{\circ}\text{C}$		
Battery	Built-in Li-on		
Charger	High quality USB charger		
Charging temp.	0°C to $+45^{\circ}\text{C}$		

Item No.	Capacity (T)	A (mm)	B (mm)	C (mm)	D (mm)	Ø (mm)	Weight (kg)
UNI-LINK02-1000S	1000 kg.	249.00	90.00	198.00	68.00	20.00	2.4
UNI-LINK02-2000S	2000 kg.	291.00	90.00	230.00	86.00	26.00	4.1
UNI-LINK02-5000S	5000 kg.	291.00	90.00	230.00	86.00	26.00	4.1

