

UNI-LINK03

Ver. 1.0

- Highly accurate and reliable.
- Very clear red digit LED display. Visible at long distances / in bright daylight.
- IP67 Classification. Ideal for wet environments.
- Designed and manufactured in Denmark for high quality assurance.
- Bluetooth allows long-range (Class 1) and short-range (Class 2) communication with Vetec App for data logging.
- Optional handheld remote display available.



Specifications	
Item No.	UNI-LINK03
Capacity	Adjustable (0-99999)
A/D conversion	10 conversions pr. sec.
Resolution	1 in 400.000 max. over full range
Display update rate	1-2,4 reading pr. sec.(Adjustable)
Filtering	Fixed
EXC voltage	3,3V
Display resolution	Adjustable
Material	PETG plastic
IP Classification	IP67
Display	Bright LED
Digit height	14 mm
Digit color	Red
Operating time	16-20 hours (Operating at low temperatures will decrease the operating time)
Operating temp.	-20°C to +50°C
Battery	Built-in Li-on
Charger	High quality USB charger
Charging temp.	0°C to +45°C

Item No.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	ØG (mm)	ØH (mm)	Weight (kg)
UNI-LINK03	112,00	90,00	26,70	105,50	53,00	30,00	3,40	3,50-5,50	0,22

