

V-Link Inox Dynamometer

Ver. 1.0

- Highly accurate and reliable, $\pm 0,2\%$ FS accuracy.
- Very clear red digit LED display. Visible at long distances / in bright daylight.
- IP67 Classification. Ideal for wet environments.
- Robust high strength Stainless Steel construction for use in hostile environments.
- Supplied with full certificate of calibration.
- Includes a durable ABS plastic hard case.
- Designed and manufactured in Denmark for high quality assurance.
- Bluetooth allows long-range (Class 1) and short-range (Class 2) communication with Vetec App for data logging.
- Optional handheld remote display available.



Specifications					
Item No.	670303	670603	671203	672503	675503
Capacity	3.25T	6.5T	12.5T	25T	55T
Accuracy	$\pm 0.2\%$ FS				
Accuracy	$\pm 7\text{kg.}^*$	$\pm 15\text{kg.}^*$	$\pm 30\text{kg.}^*$	$\pm 50\text{kg.}^*$	$\pm 150\text{kg.}^*$
Safe overload	110%				
Safe overload	3575 kg.	7150 kg.	13750 kg.	27500 kg.	60500 kg.
Breaking limit	500%				
Resolution	1 kg.	5 kg.	10 kg.	10 kg.	50 kg.
Material	High strength Stainless Steel housing.				
IP Classification	IP67				
Display	Bright LED				
Digit height	14 mm				
Digit color	Red				
Operating time	16-20 hours (Operating at low temperatures will decrease the operating time)				
Operating temp.	-20°C to $+50^{\circ}\text{C}$				
Battery	Built-in Li-on				
Charger	High quality USB-C charger				
Charging temp.	0°C to $+45^{\circ}\text{C}$				

Item No.:	Capacity (T)	A (mm)	B (mm)	C (mm)	D (mm)	Ø (mm)	Weight (kg)
670303	3.25T	230.00	93.00	170.00	33.00	20.00	2.13
670603	6.5T	275.00	120.00	190.00	38.00	27.00	5.08
671203	12.5T	300.00	125.00	200.00	38.00	37.00	6.99
672503	25T	360.00	135.00	230.00	38.00	54.00	9.73
675503	55T	460.00	175.00	280.00	50.00	74.00	22.63

*Rounded due to display resolution

